

Enable large-volume printing on a wide range of paper sizes—up to Ledger/A3—with a 4,600-sheet maximum input capacity.<sup>2</sup> Preview and edit scanning jobs. Centrally manage printing policies. Safeguard sensitive business information.

Print speed:13 Up to 40 ppm black (letter)

Print resolution: Up to 1200 x 1200 dpi black (best)

**Scan resolution:** Up to  $600 \times 600 \, \text{dpi}$  hardware, Up to  $600 \, \text{dpi}$  Optical

**Standard connectivity:** 2 Hi-Speed USB 2.0 Host, 1 Hi-Speed USB 2.0 Device, 1 Gigabit Ethernet 10/100/1000T network, 1 Foreign Interface, 1 Hardware Integration Pocket, 2 Internal USB Host

**Duplex print options:** Automatic (standard)

Mobile printing capability: HP ePrint, Apple AirPrint™



(HP LaserJet Enterprise MFP M725dn shown)



HP LaserJet Enterprise
MFP M725f

# Expand your options with sharp Ledger/A3 printing

- Empower your teams to do more—print, scan, copy, and fax¹ on paper sizes up to Ledger/A3—from a desktop-sized MFP.
- Stay focused on work—paper capacity up to 4,600 sheets and high-capacity cartridges limit interruptions.<sup>2,4</sup>
- Get impressive document quality with near edge-to-edge printing and a convenient, built-in stapler.<sup>5</sup>
- Print what you need, even on the go—from your smartphone or tablet—using HP ePrint<sup>3</sup> or Apple AirPrint™.<sup>6</sup>

### Quicken your business pace

- Streamline tasks—print, scan, copy, and fax¹ projects directly at the MFP's large color touchscreen.
- Save time by launching one-touch workflows with HP Quick Sets.
- Get just the results you need—using touchscreen controls to preview, edit, and reorder scans at the device.
- Easily send scanned files to a fax, folder, email, or USB.
   Print right from a memory device via the USB port.

# Manage and protect your fleet for the long run

- Simplify fleet management using world-class tools such as HP Web Jetadmin,<sup>7</sup> and reliably safeguard devices.
- Safeguard data—at rest or in transit—with an encrypted hard drive, user authentication, and security features.
- Add security tools—such as card and badge readers via the hardware integration pocket.<sup>8</sup>
- Extend the capabilities of workteam print environments, using a rich array of easy-to-integrate solutions.

# Help save energy and reduce environmental impact

- Reduce energy use with HP Auto-On/Auto-Off Technology,<sup>9</sup> and conserve power with Instant-on Technology.<sup>11</sup>
- Use optional HP EcoSMART Fleet to easily create and manage environmental printing policies and practices.
- Conserve resources and save paper—use automatic two-sided printing.
- Easily recycle Original HP LaserJet toner cartridges through HP Planet Partners.<sup>12</sup>

### HP EcoSolutions

- Reduce energy use with Instant-on Technology.<sup>1</sup>
- Reduce paper use by up to 50%, using automatic two-sided printing.
- Reduce waste—scan, store, and distribute documents digitally.

Join HP in more sustainable printing hp.com/ecosolutions



1 Compared with products that use traditional fusing



**HP LaserJet Enterprise** 

MFP M725z

HP LaserJet Enterprise MFP M725z+

¹Fax capabilities are available with an optional fax card on the HP LaserJet Enterprise MFP M725dn. ² Maximum paper capacity of 4,600 sheets requires the purchase of optional paper tray accessories. ³ Requires an Internet connection to HP web-enabled printer and HP ePrint accounts registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see hpconnected.com). Mobile devices require Internet connection and email capability. May require wireless escess points. Separately purchased data plans or usage fees may apply. Print times and connection speeds may vary. Some HP LaserJet printers may require firmware upgrades. ⁴ High-capacity cartridges are optional for the HP LaserJet Enterprise 700 MFP Series M725. ⁵ In-line stapler is not available on the HP LaserJet Enterprise MFP M725dn or M725f. ⁵ Supports the following devices running iOS 4.2 or later: iPad® , iPad® 2, iPhone® (3GS or later), iPod touch® (3rd generation or later). Works with HP's Air Print-enabled printers and requires the printer be connected to the same network as your iOS device. Wireless performance is dependent upon physical environment and distance from the access point. Air Print, the Air Print Logo, iPad, iPhone, and iPod touch are trademarks of Apple® inc., registered in the U.S. and other countries. ¹ HP Web be letadmin is free and can be downloaded at hp.com/go/webjetadmin. ⁵ Solutions deployed through the hardware integration pocket may require a firmware upgrade. ¹ MP EcoSMART Fleet must be purchased separately. ¹¹ Compared with products that use traditional fursing. ¹² Program availability varies. Original HP cartridge return and recycling is currently available in more than 50 countries, territories and regions in Asia, Europe, and North and South America through the HP Planer Partners program. For more information, visit: hp.com/recycle. ¹³ Measured using ISO/IEC 24734, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies dependi

### **HP LaserJet Enterprise MFP M725 series**

- 1 100-sheet automatic document feeder
- 2 Intuitive 8-inch pivoting color touchscreen control panel with FutureSmart firmware and scan preview
- 3 Hardware integration pocket (HIP) for solution integration
- 4 Easy-access USB port to save and print files directly
- 5 In-line stapler with 500-sheet output bin
- 6 Built-in automatic two-sided printing
- 7 Two 250-sheet input trays, one supporting up to legal and one supporting up to ledger/A3
- 8 3,500-sheet high-capacity feeder and stand for a 4,100-sheet total input capacity
- 9 250-sheet output bin
- 10 Side door allows convenient access to the all-in-one HP print cartridge
- 11 100-sheet multipurpose tray 1 supports a wide variety of paper sizes and types
- 12 800 MHz processor, 1 GB standard memory
- 13 Two internal USB Host ports (for connecting third-party devices)
- 14 HP High-Performance Secure Hard Disk
- 15 Fax port
- 16 Foreign Interface port
- 17 HP Jetdirect Gigabit Ethernet print server
- 18 Hi-Speed USB 2.0 device port
- 19 Hi-Speed USB 2.0 Host port

### **HP LaserJet Enterprise MFP M725z+ printer shown**



### Series at a glance









|   | M725dn MFP    | M725f MFP     | M725z MFP     | M725z+ MFP    |
|---|---------------|---------------|---------------|---------------|
| Part number   | CF066A        | CF067A        | CF068A        | CF069A        |
| Gigabit Ethernet networking                             | ✓             | ✓             | ✓             | ✓             |
| Automatic two-sided printing                            | ✓             | ✓             | ✓             | ✓             |
| 100-sheet multipurpose tray 1                           | ✓             | ✓             | ✓             | ✓             |
| 2 x 250-sheet trays 2 and 3                             | ✓             | ✓             | ✓             | ✓             |
| 500-sheet tray¹   | Optional      | ✓             | Not available | Optional      |
| 500-sheet feeder with cabinet and stand¹                | Optional      | ✓             | Not available | Not available |
| 3 x 500-sheet feeder and stand¹                         | Optional      | Not available | ✓             | Not available |
| 3,500-sheet high-capacity feeder and stand <sup>1</sup> | Optional      | Not available | Not available | ✓             |
| 500-sheet in-line stapler                               | Not available | Not available | /             | ✓             |
| HP High-Performance Secure Hard Disk                    | ✓             | ✓             | ✓             | ✓             |
| Fax   | Optional      | ✓             | ✓             | ✓             |
| ENERGY STAR® qualified                                  | <b>√</b>      | <b>√</b>      | <b>√</b>      | <b>√</b>      |

<sup>&</sup>lt;sup>1</sup> Up to 6 input trays are supported on the M725dn and M725z+ models, including the multipurpose tray and the standard 2 x 250-sheet trays. (The 3 x 500-sheet trays and stand counts for 3 trays; the 3,500-sheet HCI feeder and stand counts for 2 trays.) The 500-sheet tray is not stackable.

### **Top features**

Get precise document finishing, one-touch workflows, and many scan-to options on a versatile Ledger/A3 MFP. Do more—with document sizes up to Ledger/A3, and high-capacity cartridges³ and paper trays. Print nearly to the page's edge, and even staple (Only on Z and Z+ models). Copy, scan, and fax¹—and print from smartphones and tablets from virtually anywhere with HP ePrint.²

Set a swift pace—use this powerful MFP to keep your work moving. Save time and make your job easier, using HP Quick Sets. Preview and control jobs on the 8-inch color touchscreen. Scan to multiple locations, and print via an easy-access USB port.

Monitor your devices with industry-leading tools, including HP Web Jetadmin.<sup>4</sup> Help protect data both in transit and at rest. Enhance security with PIN printing. Add safeguards via the hardware integration pocket. Integrate tomorrow's solutions with ease.

Help conserve resources and meet corporate environmental goals. HP Auto-On/Auto-Off Technology helps reduce energy use. Easily manage printing policies with HP EcoSMART Fleet. Save paper, using automatic two-sided printing.

### Get the most out of your printer with HP accessories, supplies, and services.

### **HP** services

Downtime can have serious consequences, so HP provides support beyond the standard warranty. You benefit from reduced risk, maximized uptime, predictable service delivery and no unbudgeted repair costs. Choose from:

**Optimized Care** (optimum performance and stability):

4 hour Onsite Support, Maintenance Kit Replacement Service, Installation with Network Configuration Service

Standard Care (high level of uptime):

Next Business Day Onsite Support, Maintenance Kit Replacement Service, Installation with Network Configuration Service

Basic Care (minimum recommended support):

Next Business Day Onsite Support

**4 hr Onsite Support:** Onsite support within four hours after a service call received within the coverage window

**Next Business Day Onsite Support:** Onsite service the next business day after the service call is received

**Maintenance Kit Replacement Service:** Onsite replacement of your printer's maintenance kit including parts, materials, and labor

**Installation with Network Configuration Service:** Assembly, network configuration, and basic administrator familiarization

For more information about HP Care Pack, HP Contractual, or HP Managed Print Services, visit hp.com/go/printservices

#### **Printers**

| HP LaserJet Enterprise 700 MFP M725dn | CF066A |
|---------------------------------------|--------|
| HP LaserJet Enterprise 700 MFP M725f  | CF067A |
| HP LaserJet Enterprise 700 MFP M725z  | CF068A |
| HP LaserJet Enterprise 700 MFP M725z+ | CF069A |

#### Toner Cartridges

| HP 14A Black LaserJet Toner Cartridge (10,000 pages)  | CF214A |
|---|--------|
| HP 14X Black Laser let Toner Cartridge (17 500 pages) | CF214X |

#### Accessories

| 500-sheet feeder and tray assembly       | CF239A |
|--|--------|
| 1x500-sheet feeder, cabinet, and stand   | CF243A |
| 3x500-sheet feeder and stand             | CF242A |
| 3,500-sheet HCl and stand                | CF245A |
| 110v Maintenance/Fuser Kit               | CF249A |
| 220v Maintenance/Fuser Kit               | CF254A |
| HP 200-pin DDR2 512MBx64 DIMM            | CF306A |
| HP staple cartridge refill               | C8091A |
| HP LaserJet MFP Analog Fax Accessory 500 | CC487A |
| ADF Roller kit                           | L2718A |

#### IP Care Pack

| HP Care Pack  |         |
|---|---------|
| HP 3-year Next Business Day + DMR LaserJet M725 MFP Support               | U7A14E  |
| HP 3-year 4h 9x5 LaserJet M725 MFP Hardware Support                       | U7A08E  |
| HP 3-year 4h 13x5 LaserJet M725 MFP Hardware Support                      | U7A09E  |
| HP 2-year Post Warranty Next Business Day LaserJet M725MFP                |         |
| Hardware Support  | U7Y73PE |
| HP 1-year Post Warranty Next Business Day + DMR LaserJet M725 MFP Support | U7Y76PE |
|   |         |

To know what HP Care Pack services exist for your product, please visit Care Pack Central at hp.com/go/cpc

#### Paper

hp.com/go/paper

### Software

HP Web Jetadmin: hp.com/go/wja
HP Universal Print Driver: hp.com/go/upd

<sup>&</sup>lt;sup>1</sup> Fax capabilities are available with an optional fax card on the HP Laser Jet Enterprise MFP M725dn. <sup>2</sup> Requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see <a href="https://hpconnected.com">hpconnected.com</a>). Mobile devices require Internet connection and email capability. May require wireless access point. Separately purchased data plans or usage fees may apply. Print times and connection speeds may vary. Some HP Laser Jet printers may require firmware upgrades. <sup>3</sup> High-capacity cartridges are optional for the HP Laser Jet Enterprise 700 MFP Series M725. <sup>4</sup> HP Web Jetadmin is free and can be downloaded at <a href="hp.com/go/webjetadmin.5">hp.com/go/webjetadmin.5</a> HP Auto-On/Auto-Off Technology capabilities subject to printer and settings; may require a firmware upgrade. <sup>4</sup> HP EcoSMART Fleet must be purchased separately.

## **HP LaserJet Enterprise MFP M725 series**

|  | HP LaserJet Enterprise 700 MFP M725dn<br>(CF066A)  | HP LaserJet Enterprise 700 MFP M725f<br>(CF067A)   | HP LaserJet Enterprise 700 MFP M725z<br>(CF068A)   | HP LaserJet Enterprise 700 MFP M725z+<br>(CF069A)  |
|--|--|--|--|--|
| AIO functions  | Print, copy, scan  |  | Print, copy, scan, fax   |  |
| Print  |  |  |  |  |
| Duplex print options   |  |  | c (standard)   |  |
| Print speed <sup>1</sup>   |  | Up to 40 ppm (Black, letter); <b>F</b>   | irst page out²: As fast as 10 sec  |  |
| Print technology   |  | Li   | eser   |  |
| Print resolution   | Black (best): Up to 120  | 00 x 1200 dpi; <b>Black (normal):</b> HP FastRes 1200 (1   | 200 dpi quality), 600 x 600 dpi with HP Resol  | ution Enhancement technology   |
| Printer Smart Software   | UD oBrint Apple Airl   | Print, Open Extensibility Platform, FutureSmart Firm   | nuaro HB Auto On/Auto Off tochnology Fac   | Accord USB Imago Brovious  |
| features   | nr erilli, apple all r   | rint, Open Extensibility Flatform, Futuresinalt Fill   | nware, nr Auto-On/Auto-On technology, Eas  | sy Access 03B, illiage Fleview   |
| Mobile printing capability   |  | HP ePrint; i   | Apple AirPrint   |  |
| Standard print languages   |  | HP PCL 6; HP PCL 5e; HP pos  | stscript level 3 emulation; PDF  |  |
| ican   |  |  |  |  |
| Scan type/technology   |  | Flatbed, ADF; <b>Technology:</b>   | Charge Coupled Device (CCD)  |  |
| Scan speed <sup>3</sup>  |  | Letter: Up to 49 ppm (black a  | and white), up to 30 ppm (color)   |  |
| Scan resolution  |  | Hardware: Up to 600 x 60   | 0 dpi; <b>Optical:</b> Up to 600 dpi   |  |
| Scan file format   |  | PDF, JPEG, TIFF,   | MTIFF, XPS, PDF/A  |  |
| Scan input modes   | Copy, scan to e  | -mail, scan to network folder, scan to USB, save to  | device memory, fax, Open Extensibility Platf   | orm (OXP) applications   |
| Scan size maximum  |  | ADF, Flatbed: 11 x   | 17 in (297 x 420 mm)   |  |
|  | Optimize text/picture; Image adjustments; J  |  |  | ge erase; Auto tone; Auto job notification; Blank page   |
| Scanner advanced features  |  |  | HP Quick Sets  |  |
| Bit depth/Grayscale levels   |  | 24 b   | it/256   |  |
| ору  |  |  |  |  |
| Copy speed <sup>4</sup>  |  | Up to 40 con   | n (Black, letter)  |  |
| Copy resolution  |  |  | phics): 600 x 600 dpi  |  |
| Max number of copies   |  |  | 999 copies   |  |
| Copier reduce/enlarge  |  |  | 0 400%   |  |
| Copier settings  | Sides: Collate: Paper Selection: Poduce  | Enlarge; Image Adjustment; Content Orientation; F  |  | e: Ontimize Text/Picture: Original Size: Joh Build   |
|  | Sides, collate, Paper Selection, Reduce,   | Entarge, image Aujustment, content orientation, F  | ages per sneet, booklet format, edge to edg  | e, Optimize Text/Ficture, Original Size, Job Build   |
| Digital Sending Standard<br>features   | Scan to e-mail; Save-t   | o-Network Folder; Save-to-USB drive; Send to FTP   | ; Send to LAN Fax; Send to Internet Fax; Local   | l Address Book; SMTP over SSL  |
| ax   |  |  |  |  |
| Transmission speed <sup>s</sup>  | Not Applicable   |  | Up to 33.6 kbps; 3 sec per page  |  |
| rransmission speed   | ног аррисане   | Plack (host): Up to 200 v 200 dpi (400 v 400   |  | 1): 204 x 98 dpi; Black and White (fine): 204 x 196 dpi,   |
| Fax resolution   | Not Applicable   |  | lack Photo Grayscale: 300 x 300 dpi (400 x 4   |  |
| Fax smart software   | Not Applicable   |  | •  | t fax; fax number confirmation; Holiday fax schedule   |
| features<br>Fax memory   | Not Applicable   |  | Up to 100 pages  |  |
| ·  | Not Applicable   |  | dialing: Yes; Fax Delayed Sending: No; Disti   | inctive Ring Detection Supported: No; Fax Forwarding<br>to receive only); Junk Barrier Supported: Yes; PC Interf   |
| Fax features   | нот аррисавіе  |  | ortea: No; rax rolling Supportea: Yes (poll t  |  |
|  |  | Supported: Yes; T  | elephone Handset Supported: No; Fax Tele   |  |
| Connectivity   |  | Supported: Yes; T  |  |  |
| •  | 2 Hi-Speed USB 2.0 Host: 1 Hi-S  | ••   | elephone Handset Supported: No; Fax Tele   | phone Mode Supported: No   |
| Standard connectivity  |  | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10  | elephone Handset Supported: No; Fax Tele<br>100T network; 1 Foreign Interface; 1 Hardwar   | phone Mode Supported: No<br>e Integration Pocket; 2 Internal USB Host  |
| · · · · · · · · · · · · · · · · · · ·  |  | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10<br>r (standard) supports: 10Base-T, 100Base-Tx, 100C   | elephone Handset Supported: No; Fax Tele<br>100T network; 1 Foreign Interface; 1 Hardwar   | phone Mode Supported: No<br>e Integration Pocket; 2 Internal USB Host  |
| Standard connectivity  |  | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10<br>r (standard) supports: 10Base-T, 100Base-Tx, 100C<br>networki   | elephone Handset Supported: No; Fax Tele<br>00T network; 1 Foreign Interface; 1 Hardwar<br>1Base-T; 802.3az (EEE) support on Fast Ether  | phone Mode Supported: No<br>e Integration Pocket; 2 Internal USB Host  |
| Standard connectivity  Network capabilities  Wireless capability   | Via HP Jetdirect Ethernet embedded print serve   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10<br>r (standard) supports: 10Base-T, 100Base-Tx, 100C<br>networki   | elephone Handset Supported: No; Fax Telej<br>100T network; 1 Foreign Interface; 1 Hardwar<br>1Base-T; 802.3az (EEE) support on Fast Ether<br>1g (optional)<br>chase of a hardware accessory  | phone Mode Supported: No<br>e Integration Pocket; 2 Internal USB Host  |
| Standard connectivity  Network capabilities  Wireless capability  Modem  |  | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10<br>r (standard) supports: 10Base-T, 100Base-Tx, 100C<br>networki<br>Optional, enabled with purc  | elephone Handset Supported: No; Fax Telej<br>000T network; 1 Foreign Interface; 1 Hardwar<br>1Base-T; 802.3az (EEE) support on Fast Ether<br>1g (optional)<br>chase of a hardware accessory<br>33.6 kbps   | phone Mode Supported: No   |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Memory  | Via HP Jetdirect Ethernet embedded print serve   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10<br>r (standard) supports: 10Base-T, 100Base-Tx, 100C<br>networki<br>Optional, enabled with purc  | elephone Handset Supported: No; Fax Telej<br>00T network; 1 Foreign Interface; 1 Hardwar<br>18ase-T; 802.3az (EEE) support on Fast Ether<br>19 (optional)<br>chase of a hardware accessory<br>33.6 kbps  | phone Mode Supported: No<br>e Integration Pocket; 2 Internal USB Host  |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Memory  Processor speed   | Via HP Jetdirect Ethernet embedded print serve   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10<br>r (standard) supports: 10Base-T, 100Base-Tx, 100C<br>networkin<br>Optional, enabled with purc<br>1<br>80  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar iBase-T; 802.3az (EEE) support on Fast Ether ig (optional) chase of a hardware accessory 33.6 kbps GB 0 MHz  | phone Mode Supported: No<br>e Integration Pocket; 2 Internal USB Host  |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Memory  Processor speed  Duty cycle (monthly, A4) <sup>6</sup>  | Via HP Jetdirect Ethernet embedded print serve   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10<br>r (standard) supports: 10Base-T, 100Base-Tx, 100C<br>networki<br>Optional, enabled with pure<br>1<br>80<br>Up to 200  | elephone Handset Supported: No; Fax Telej<br>00T network; 1 Foreign Interface; 1 Hardwar<br>IBase-T; 802.3az (EEE) support on Fast Ether<br>19 (optional)<br>chase of a hardware accessory<br>33.6 kbps<br>GB<br>0 MHz<br>2,000 pages  | phone Mode Supported: No<br>e Integration Pocket; 2 Internal USB Host  |
| Standard connectivity  Network capabilities  Wireless capability  Modern  Memory  Processor speed  Duty cycle (monthly, A4) <sup>6</sup> Recom monthly page volume <sup>7</sup>  | Via HP Jetdirect Ethernet embedded print serve   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10<br>r (standard) supports: 10Base-T, 100Base-Tx, 100C<br>networki<br>Optional, enabled with pure<br>1<br>80<br>Up to 200  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar iBase-T; 802.3az (EEE) support on Fast Ether ig (optional) chase of a hardware accessory 33.6 kbps GB 0 MHz  | phone Mode Supported: No<br>e Integration Pocket; 2 Internal USB Host  |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Memory  Processor speed  Duty cycle (monthly, A4) <sup>6</sup> Recom monthly page volume <sup>7</sup> Paper handing   | Via HP Jetdirect Ethernet embedded print serve<br>Not Applicable   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10<br>r (standard) supports: 10Base-T, 100Base-Tx, 100C<br>networki<br>Optional, enabled with purc<br>1<br>80<br>Up to 200<br>Up to 5000 t  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1 chase of a hardware accessory 33.6 kbps 1 GB 1 MHz 1 0,000 pages 2 0 20,000 pages   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host net and Gig Links; IPsec (standard); 802.11b/g/n wirele   |
| Standard connectivity  Network capabilities  Wireless capability Modem Memory Processor speed Juty cycle (monthly, A4) <sup>6</sup> lecom monthly page volume <sup>7</sup> Paper handing Media type  | Via HP Jetdirect Ethernet embedded print serve<br>Not Applicable   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure 1 80 Up to 200 Up to 5000 t ad, light, plain, preprinted, prepunched, recycled, re   | elephone Handset Supported: No; Fax Telep 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1 chase of a hardware accessory 1 33.6 kbps 1 GB 2 MHz 2,000 pages 2 0 20,000 pages 2 0 000,000 pages 3 0 000,000 pages   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host net and Gig Links; IPsec (standard); 802.11b/g/n wirele   |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Alemory  Oroccssor speed  luty cycle (monthly, A4) <sup>6</sup> lecom monthly page volume <sup>7</sup> Paper handing  Media type  Media weight  | Via HP Jetdirect Ethernet embedded print serve<br>Not Applicable   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networki Optional, enabled with pure 80 Up to 200 Up to 5000 t Up to 5000 t Tray 1: 16 to 53 lb (60 to 199 g/m²);  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1. chase of a hardware accessory 33.6 kbps 6B 0 MHz 0,000 pages 0 20,000 pages 0 ugh, tough paper), bond, cardstock, envelop Trays 2-6: 16 to 32 lb (60 to 120 g/m²)  | phone Mode Supported: No re Integration Pocket; 2 Internal USB Host net and Gig Links; IPsec (standard); 802.11b/g/n wirele the standard of th |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Memory  Processor speed  Puty cycle (monthly, A4) <sup>a</sup> Recom monthly page volume <sup>7</sup> Paper handing  Media type  Media weight  Custom media sizes   | Via HP Jetdirect Ethernet embedded print serve<br>Not Applicable   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networki Optional, enabled with pure 1 80 Up to 200 Up to 5000 Up to 5000 tad, light, plain, preprinted, prepunched, recycled, re Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t   | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar (Base-T; 802.3az (EEE) support on Fast Ether (g (optional) chase of a hardware accessory  33.6 kbps (GB 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 ugh, tough paper), bond, cardstock, envelop Trays 2-6: 16 to 32 lb (60 to 120 g/m²) 0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7   | phone Mode Supported: No re Integration Pocket; 2 Internal USB Host net and Gig Links; IPsec (standard); 802.11b/g/n wirele the standard of th |
| Standard connectivity  Network capabilities  Wireless capability  Modem  **Jemory  **Jemory  **Jerocessor speed  **Juty cycle (monthly, A4)**  **Jecom monthly page volume*  **Paper handing  **Media type  **Media type  **Media weight   | Via HP Jetdirect Ethernet embedded print serve<br>Not Applicable   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networki Optional, enabled with pure 1 80 Up to 200 Up to 5000 Up to 5000 tad, light, plain, preprinted, prepunched, recycled, re Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t   | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1. chase of a hardware accessory 33.6 kbps 6B 0 MHz 0,000 pages 0 20,000 pages 0 ugh, tough paper), bond, cardstock, envelop Trays 2-6: 16 to 32 lb (60 to 120 g/m²)  | phone Mode Supported: No re Integration Pocket; 2 Internal USB Host net and Gig Links; IPsec (standard); 802.11b/g/n wireles   |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Aemory  Processor speed  Puty cycle (monthly, A4) <sup>s</sup> Recom monthly page volume <sup>7</sup> Paper handing  Media type  Media weight  Custom media sizes  ADF capacity   | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhed)  24.2 × 25.6 × 24 in (614 × 649 × 609 mm)   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 1000 networkin Optional, enabled with pure  1 80 Up to 200 Up to 5000 t Up to 5000 t  ad, light, plain, preprinted, prepunched, recycled, re  Tray 1: 16 to 53 lb (60 to 199 g/m²);  Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t  \$29.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm);   | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1. chase of a hardware accessory 33.6 kbps 6B 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 ugh, tough paper), bond, cardstock, envelop 17ays 2-6: 16 to 32 lb (60 to 120 g/m²) 0 11.7 x 14.3 in; 17ays 3-6: 5.8 x 8.3 to 11.7 100 sheets 29.3 x 26.8 x   | phone Mode Supported: No re Integration Pocket; 2 Internal USB Host net and Gig Links; IPsec (standard); 802.11b/g/n wireles re, labels, transparency, vellum x 17 in 46.9 in (745 x 681 x 1192 mm);   |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Alemory  Processor speed  Juty cycle (monthly, A4) <sup>6</sup> Lecom monthly page volume <sup>7</sup> Paper handing  Media type  Media type  Media weight  Custom media sizes  ADF capacity  Dimensions (W x D x H)  | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhed)  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networki Optional, enabled with pure 1 800 Up to 200 Up to 5000 t ad, light, plain, preprinted, prepunched, recycled, re Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t \$tandard 29.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm); Max: 36.1 x 40.6 x 45.7 in (917 x 1032 x 1160 mm);  | elephone Handset Supported: No; Fax Telej 000T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1.chase of a hardware accessory 33.6 kbps 68 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 10 pages 10 pages 10 pages 11 page 12 page 13 page 14 page 15 p | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wireles  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm); x 46.9 in (917 x 1032 x 1192 mm)  |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Alemory  Processor speed  Juty cycle (monthly, A4) <sup>6</sup> Lecom monthly page volume <sup>7</sup> Paper handing  Media type  Media type  Media weight  Custom media sizes  ADF capacity  Dimensions (W x D x H)  | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhed)  24.2 × 25.6 × 24 in (614 × 649 × 609 mm)  Max: 34.1 × 38.9 × 24 in (865 × 989 × 609 mm)  119.3 lb (54.11 kg)   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure  1 80: Up to 200 Up to 5000 t Up to 5000 t Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 × 5 to 12.3 × 18.5 in; Tray 2: 5.8 × 8.3 t Standard 29.3 × 26.8 × 45.7 in (745 × 681 × 1160 mm); Max: 36.1 × 40.6 × 45.7 in (917 × 1032 × 1160 mm) 192.3 lb (87.1 kg)   | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 0Base-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1 chase of a hardware accessory 33.6 kbps 6B 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 1,100 sheets 29.3 x 26.8 x Max: 36.1 x 40.6 206.3 lb (92.35 kg)   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host net and Gig Links; IPsec (standard); 802.11b/g/n wirele:  net a |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Alemory  Processor speed  Processor   | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhed)  24.2 × 25.6 × 24 in (614 × 649 × 609 mm)  Max: 34.1 × 38.9 × 24 in (865 × 989 × 609 mm)  119.3 lb (54.11 kg)   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure 1 80 Up to 200 Up to 5000 t Up to 5000 t  ad, light, plain, preprinted, prepunched, recycled, re Tray 1: 16 to 53 lb (50 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8: 3 Standard 29.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm); Max: 36.1 x 40.6 x 45.7 in (917 x 1032 x 1160 mm) 192.3 lb (87.1 kg)  4P Black LaserJet Toner Cartridge (10,000 pages); i   | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1 chase of a hardware accessory   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wireles  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm); x 46.9 in (917 x 1032 x 1192 mm)  |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Alemory  Processor speed  Processor   | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhed)  24.2 × 25.6 × 24 in (614 × 649 × 609 mm)  Max: 34.1 × 38.9 × 24 in (865 × 989 × 609 mm)  119.3 lb (54.11 kg)   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure 1 80 Up to 200 Up to 5000 t Up to 5000 t  ad, light, plain, preprinted, prepunched, recycled, re Tray 1: 16 to 53 lb (50 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8: 3 Standard 29.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm); Max: 36.1 x 40.6 x 45.7 in (917 x 1032 x 1160 mm) 192.3 lb (87.1 kg)  4P Black LaserJet Toner Cartridge (10,000 pages); i   | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 0Base-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1 chase of a hardware accessory 33.6 kbps 6B 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 1,100 sheets 29.3 x 26.8 x Max: 36.1 x 40.6 206.3 lb (92.35 kg)   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host net and Gig Links; IPsec (standard); 802.11b/g/n wirele:  net a |
| Standard connectivity  Network capabilities  Wireless capability  Modem  **Jemory  Torocessor speed  Duty cycle (monthly, A4)**  Recom monthly page volume*  Paper handing  Media type  Media weight  Custom media sizes  ADF capacity  Dimensions (W x D x H)  Weight  What's in the box*   | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhed)  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; I  | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networki Optional, enabled with pure  1 80: Up to 200 Up to 5000t Up to 5000t Up to 5000t Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t 23.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm); Max: 36.1 x 40.6 x 45.7 in (917 x 1032 x 1160 mm) 192.3 lb (87.1 kg)  IP Black LaserJet Toner Cartridge (10,000 pages); CD-ROM; Power cord. M725f, M725z & N One-year or   | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1. chase of a hardware accessory 33.6 kbps 6B 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 1,100 sheets 29.3 x 26.8 x Max: 36.1 x 40.6 206.3 lb (92.35 kg) 1.4ardware Installation by Telecom cable 1-site warranty  | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wireles  i.e., labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm); x 46.9 in (917 x 1032 x 1192 mm)  225.8 lb (102.42 kg) arranty guide; Printer documentation and software on   |
| Standard connectivity  Network capabilities  Wireless capability Modem Memory Processor speed Outy cycle (monthly, A4) <sup>6</sup> Recom monthly page volume <sup>7</sup> Paper handling Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box <sup>6</sup> Warranty features   | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhed)  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP LaserJet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windows 1, Windows  | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure  1 80 Up to 200 Up to 5000 t Up to 5000 t Up to 5000 t Up to 5000 t 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t Standard 29.3 x 26.8 x 45.7 in (7745 x 681 x 1160 mm); Max: 36.1 x 40.6 x 45.7 in (917 x 1032 x 1160 mm); 192.3 lb (87.1 kg) HP Black Laser Jet Toner Cartridge (10,000 pages); 1 (CD-ROM; Power cord. M725f, M725s, 2M One-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1: chase of a hardware accessory 33.6 kbps 6B 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 ugh, tough paper), bond, cardstock, envelop 17ays 2-6: 16 to 32 lb (60 to 120 g/m²) 0 11.7 x 14.3 in; 17ays 3-6: 5.8 x 8.3 to 11.7 1,00 sheets 29.3 x 26.8 x Max: 36.1 x 40.6 206.3 lb (92.35 kg) 1-ardware Installation Guide, Support flyer, W. 1725z+: Same as above plus Telecom cable 1-site warranty Server 2008 (32 and 64-bit), Windows Server 2  | phone Mode Supported: No re Integration Pocket; 2 Internal USB Host net and Gig Links; IPsec (standard); 802.11b/g/n wireles re, labels, transparency, vellum x 17 in 46.9 in (745 x 681 x 1192 mm); x 46.9 in (917 x 1032 x 1192 mm) 225.8 lb (102.42 kg) arranty guide; Printer documentation and software on  |
| Standard connectivity  Network capabilities  Wireless capability Modern Memory Processor speed Duty cycle (monthly, A4) <sup>5</sup> Recom monthly page volume <sup>7</sup> Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box <sup>6</sup> Warranty features Compatible operating  | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhei  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; I  Windows 8, Windows 7, Windows Vista, Windov 10.6, OS X Lion, OS X Mountain Lion; For the lates   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networki Optional, enabled with pure 1 80 Up to 200 Up to 5000 t  ad, light, plain, preprinted, prepunched, recycled, re Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t 5tandard 29.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm); Max: 36.1 x 40.6 x 45.7 in (917 x 1032 x 1160 mm) 192.3 lb (87.1 kg) HP Black Laser Jet Toner Cartridge (10,000 pages); (D-ROM; Power cord. M725f, M725z & N One-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows t t operating system support see: Citrix and Windows t  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1. hase of a hardware accessory   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wirele  se, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)  |
| Standard connectivity  Network capabilities  Wireless capability Modern Memory Processor speed Duty cycle (monthly, A4) <sup>5</sup> Recom monthly page volume <sup>7</sup> Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box <sup>6</sup> Warranty features Compatible operating  | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhed)  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; I  Windows 8, Windows 7, Windows Vista, Windows 10.6, OS X Lion, OS X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/unixmodelscript | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure  10 80: Up to 5000 Up to 5000 Up to 5000 Up to 5000 Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t 23.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm); Max: 36.1 x 40.6 x 45.7 in (917 x 1032 x 1160 mm); 192.3 lb (87.1 kg)  4P Black LaserJet Toner Cartridge (10,000 pages); CD-ROM; Power cord. M725f, M725z & N One-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows t operating system support see: Citrix and Windows T etdirectunix_software); SAP device types (hp.com  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1 chase of a hardware accessory   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; iPsec (standard); 802.11b/g/n wirele  i.e, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)   |
| Standard connectivity  Network capabilities  Wireless capability Modem Alemory Forcessor speed Outy cycle (monthly, A4)s Recom monthly page volume? Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the boxs Warranty features Compatible operating yetems   | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhed)  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; I  Windows 8, Windows 7, Windows Vista, Windows 10.6, OS X Lion, OS X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/unixmodelscript | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure  1 80 Up to 200 Up to 5000 t Up to 5000 t Up to 5000 t Up to 5000 t 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t Standard 29.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm); Max: 36.1 x 40.6 x 45.7 in (917 x 1032 x 1160 mm) 192.3 lb (87.1 kg) HP Black Laser Jet Toner Cartridge (10,000 pages); 1 (D-ROM; Power cord. M725f, M725f, M725s & M One-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows to operating system support see: Citrix and Windows T etdirectunix_software); SAP device types (hp.com ows XP (SP2+), Windows Server 2003 (SP1+), Windows | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1: chase of a hardware accessory 33.6 kbps 68 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 ; 1.00 sheets 29.3 x 26.8 x Max: 36.1 x 40.6 206.3 lb (92.35 kg) 1-3rdware Installation Guide, Support flyer, W.1725z+ Same as above plus Telecom cable 1-site warranty Server 2008 (32 and 64-bit), Windows Server 2 1 complex pow Server 2008 R2; how Server 2008 R2, how Server 2008 R2, windows Server 2008 R2;   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wirele  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)  |
| Standard connectivity  Network capabilities  Wireless capability Modem Memory Processor speed Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H)  Veight Warranty features Compatible operating systems  Vinimum system  | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhed)  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; l  Windows 8, Windows 7, Windows Vista, Windows 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unkmodelscripts, hp.com/go/upplicable pC: Windows 8, Windows 7, Windows Vista, Windows PC: Windows 8, Windows 7, Windows Vista, Windows | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networki Optional, enabled with pure  10 80 Up to 200 Up to 5000 t  ad, light, plain, preprinted, prepunched, recycled, re Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t  Standard 29.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm); Max: 36.1 x 40.6 x 45.7 in (917 x 1032 x 1160 mm) 192.3 lb (87.1 kg)  4P Black LaserJet Forer Cartridge (10,000 pages); (CD-ROM; Power cord. M725f, M7252 & N One-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows t operating system support see: Citrix and Windows T stdirectunix_software); SAP device types (hp.com ows XP (SP2+), Windows Server 2003 (SP1+), Windows space; operating system compatible hardw space; operating system compatible hardw  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1. hase of a hardware accessory   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wirele  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)  225.8 lb (102.42 kg)  arranty guide; Printer documentation and software on  2008 R2 (64-bit), Windows Server 2012 (64-bit); Mac OS X  vell.com/iprint); Linux (hplip.net); UNIX (hp.com/go/unix ePrint Mobile Driver (hp.com/go/eprintmobiledriver)  Windows Server 2012 (64-bit); 200 MB available hard dn.:   |
| Standard connectivity  Network capabilities  Wireless capability Modem Memory Processor speed Duty cycle (monthly, A4) <sup>6</sup> Recom monthly page volume <sup>7</sup> Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box <sup>6</sup> Warranty features Compatible operating systems  Valinimum system   | Not Applicable  Paper (color, letterher  Paper (color, letterher  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 ib (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; I  Windows 8, Windows 7, Windows Vista, Windows 10.6, OS X Lion, OS X Mountain Lion; For the lates hp.com/go/unkmodelscripts, hp.com/go/pl/  PC: Windows 8, Windows 7, Windows Vista, Windows Vista, Windows 7, Windows Vista, Windows Vista, Windows Vista, Windows 7, Windows Vista, Windows Vista | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure  10 80: Up to 200 Up to 5000 Up to 5000 Up to 5000 Up to 5000 Tray 1: 3 × 5 to 12.3 × 18.5 in; Tray 2: 5.8 × 8.3 t Standard 29.3 × 26.8 × 45.7 in (745 × 681 × 1160 mm); 192.3 lb (87.1 kg) 19 Black LaserJet Toner Cartridge (10,000 pages); CD-ROM; Power cord. M725f, M725z & N 0ne-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows to operating system support see: Citrix and Windows Tetdirectunix, software); SAP device to greating system support see: Citrix and Windows Tetdirectunix, software); SAP device to greating system compatible hardw in Lion; 1 68 available hard disk space; operating system compatible hardw in Lion; 1 68 available hard disk space; operating system compatible hardw in Lion; 1 68 available hard disk space; operating system compatible hardw in Lion; 1 68 available hard disk space; operating system compatible hardw in Lion; 1 68 available hard disk space; operating system compatible hardw   | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1-hase of a hardware accessory 33.6 kbps  GB 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 1, 100 sheets 29.3 x 26.8 x Max: 36.1 x 40.6 206.3 lb (92.35 kg) 1-ardware Installation Guide, Support flyer, Width of the State of  | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host net and Gig Links; IPsec (standard); 802.11b/g/n wirele  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)  |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Vemory  Processor speed  Outy cycle (monthly, A4) <sup>6</sup> Recom monthly page volume <sup>7</sup> Paper handing  Media type  Media weight  Custom media sizes  ADF capacity  Dimensions (W x D x H)  Weight  What's in the box <sup>6</sup> Warranty features  Compatible operating cystems  Alinimum system equirements  | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhed)  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; I  Windows 8, Windows 7, Windows Vista, Windows 10.6, OS X Lion, OS X Mountain Lion; For the lates hp.com/go/unkmodelscripts, hp.com/go/Ji  PC: Windows 8, Windows 7, Windows Vista, Windows Vista, Windows 7, Windows 7, Windows Vista, Windows 7, Windows 7, Windows Vista, Windows 7, Windows 7, Windows 7, Windows 10, St. Mountain 105 internal TrueType fonts scalable in HP PCL, 9  | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure  1 80 Up to 200 Up to 5000 t Standard Standard Standard Standard 29.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm); Max: 36.1 x 40.6 x 45.7 in (917 x 1032 x 1160 mm); 192.3 b (87.1 kg) HP Black Laser Jet Toner Cartridge (10,000 pages); 1 (D-ROM; Power cord. M725f, M725x & M One-year or us XP (SP2+), Windows Server 2003 (SP1+), Windows to operating system support see: Citrix and Windows T directions of Space; operating system compatible hardwin Space; operating system compatible hardwin Lion; 1 GB available hard disk space; operating system compatible hardwin Lion; 1 GB available hard disk space; operating system compatible hardwin Lion; 1 GB available hard disk space; operating s   | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1 chase of a hardware accessory   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wireles  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)   |
| Standard connectivity  Network capabilities  Wireless capability Modem  Memory  Processor speed Outy cycle (monthly, A4) <sup>6</sup> Network capability  Media type Media type Media weight Custom media sizes ADF capacity  Dimensions (W x D x H)  Weight  What's in the box <sup>6</sup> Warranty features  Compatible operating cystems  Alinimum system  equirements  Fonts and Typefaces  | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhei  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; I  Windows 8, Windows 7, Windows Vista, Windov 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/ip  PC: Windows 8, Windows 7, Windows Vista, Windows Wista, Windows Vista, Windows 7, Windows Vista, Windows Nista, Windows  | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networki Optional, enabled with pure  10 80 Up to 5000 t  11 12 13 14 15 16 16 17 17 17 16 16 17 17 17 16 16 17 17 17 18 18 18 18 18 18 18 18 18 18 18 18 18   | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1 chase of a hardware accessory   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wireles  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)   |
| Standard connectivity  Network capabilities  Wireless capability Modern Memory Processor speed Duty cycle (monthly, A4) <sup>5</sup> Recom monthly page volume <sup>7</sup> Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box <sup>4</sup> Warranty features Compatible operating systems Minimum system equirements Fonts and Typefaces Control panel   | Not Applicable  Paper (color, letterhei  Paper (color, letterhei  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; l  Windows 8, Windows 7, Windows Vista, Window 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/Ji  PC: Windows 8, Windows 7, Windows Vista, Window 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/Ji  PC: Windows 8, Windows 7, Windows Vista, Windows Vista, Windows 7, Windows Vista, Windows Vista, Windows 105 internal TrueType fonts scalable in HP CL, 5 Vista 8 Fonts (Calibri, Cambria); addition 105 Vista 8 Fonts (Calibri, Cambri | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networki Optional, enabled with pure  10 80i Up to 200 Up to 5000 Up to 5000 Up to 5000 Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t Standard 29.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm) 192.3 lb (87.1 kg) HBack LaserJet Toner Cartridge (10,000 pages); (CD-ROM; Power cord. M725f, M7252 & N One-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows t operating system support see: Citrix and Windows T etdirectunix_software); SAP device types (hp.com ows XP (SP2+), Windows Server 2003 (SP1+), Windo space; operating system compatible hardw in Lion; 1 GB available hard disk space; operating s 2 internal scalable fonts in HP Postscript level 3 en onal font solutions available via third-party flash in r; rotating (adjustable angle) display; illuminated H  | elephone Handset Supported: No; Fax Telej  00T network; 1 Foreign Interface; 1 Hardwar  Base-T; 802.3az (EEE) support on Fast Ether  19 (optional)  chase of a hardware accessory  33.6 kbps  GB  0 MHz  0,000 pages  0 20,000 pages  0 20,000 pages  10 1,7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7, 100 sheets  29.3 x 26.8 x  Max: 36.1 x 40.6  206.3 lb (92.35 kg)  Hardware Installation Guide, Support flyer, W  17252+: Same as above plus Telecor Robe  19 server 2008 (32 and 64-bit), Windows Server 2  20 are system requirements, Server 2008 R2  are system requirements, Server 2008 R2  yestem compatible hardware system requiren  ulation (Euro symbol built-in); 1 internal USI  fromory Cards, HD Laser Jet Fonts and IPDS intermory cards, HD Las | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wireles  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)  225.8 lb (102.42 kg)  arranty guide; Printer documentation and software on  2008 R2 (64-bit), Windows Server 2012 (64-bit); Mac OS X  vell.com/iprint); Linux (hplip.net); UNIX (hp.com/go/unix ePrint Mobile Driver (hp.com/go/eprintmobiledriver)  Windows Server 2012 (64-bit); 200 MB available hard dn: nents, CD-ROM/DVD-ROM or Internet, see apple.com icode Fonts (Andale Mono WorldType); 2 Internal Windo mulation available at hp.com/go/laserjetfonts enu); Easy Access USB; Hardware Integration Pocket   |
| Standard connectivity  Network capabilities  Wireless capability Modern Memory Processor speed Duty cycle (monthly, A4) <sup>5</sup> Recom monthly page volume <sup>7</sup> Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box <sup>4</sup> Warranty features Compatible operating systems Minimum system equirements Fonts and Typefaces Control panel   | Not Applicable  Paper (color, letterhei  Paper (color, letterhei  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; l  Windows 8, Windows 7, Windows Vista, Window 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/Ji  PC: Windows 8, Windows 7, Windows Vista, Window 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/Ji  PC: Windows 8, Windows 7, Windows Vista, Windows Vista, Windows 7, Windows Vista, Windows Vista, Windows 105 internal TrueType fonts scalable in HP CL, 5 Vista 8 Fonts (Calibri, Cambria); addition 105 Vista 8 Fonts (Calibri, Cambri | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networki Optional, enabled with pure  10 80 Up to 5000 t  11 12 13 14 15 16 16 17 17 17 16 16 17 17 17 16 16 17 17 17 18 18 18 18 18 18 18 18 18 18 18 18 18   | elephone Handset Supported: No; Fax Telej  00T network; 1 Foreign Interface; 1 Hardwar  Base-T; 802.3az (EEE) support on Fast Ether  19 (optional)  chase of a hardware accessory  33.6 kbps  GB  0 MHz  0,000 pages  0 20,000 pages  0 20,000 pages  10 1,7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7, 100 sheets  29.3 x 26.8 x  Max: 36.1 x 40.6  206.3 lb (92.35 kg)  Hardware Installation Guide, Support flyer, W  17252+: Same as above plus Telecor Robe  19 server 2008 (32 and 64-bit), Windows Server 2  20 are system requirements, Server 2008 R2  are system requirements, Server 2008 R2  yestem compatible hardware system requiren  ulation (Euro symbol built-in); 1 internal USI  fromory Cards, HD Laser Jet Fonts and IPDS intermory cards, HD Las | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wireles  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)  225.8 lb (102.42 kg)  arranty guide; Printer documentation and software on  2008 R2 (64-bit), Windows Server 2012 (64-bit); Mac OS X  vell.com/iprint); Linux (hplip.net); UNIX (hp.com/go/unix ePrint Mobile Driver (hp.com/go/eprintmobiledriver)  Windows Server 2012 (64-bit); 200 MB available hard dn: nents, CD-ROM/DVD-ROM or Internet, see apple.com icode Fonts (Andale Mono WorldType); 2 Internal Windo mulation available at hp.com/go/laserjetfonts enu); Easy Access USB; Hardware Integration Pocket   |
| Standard connectivity  Network capabilities  Wireless capability Modern Memory Processor speed Duty cycle (monthly, A4) <sup>a</sup> Recom monthly page volume <sup>7</sup> Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box <sup>a</sup> Warranty features Compatible operating systems Minimum system equirements Fonts and Typefaces Control panel Software included   | Not Applicable  Paper (color, letterhei  Paper (color, letterhei  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; l  Windows 8, Windows 7, Windows Vista, Window 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/Ji  PC: Windows 8, Windows 7, Windows Vista, Window 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/Ji  PC: Windows 8, Windows 7, Windows Vista, Windows Vista, Windows 7, Windows Vista, Windows Vista, Windows 105 internal TrueType fonts scalable in HP CL, 5 Vista 8 Fonts (Calibri, Cambria); addition 105 Vista 8 Fonts (Calibri, Cambri | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networki Optional, enabled with pure 1 80 Up to 5000 t ad, light, plain, preprinted, prepunched, recycled, re Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t Standard 29.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm); 192.3 lb (87.1 kg) 4P Black LaserJet Forer Cartridge (10,000 pages); (CD-ROM; Power cord. M725f, M7252 & N One-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows t operating system support see: Citrix and Windows T stdirectunix_software); SAP device types (hp.com ows XP (SP2+), Windows Server 2003 (SP1+), Windows t operating system support see: Citrix and Windows T stdirectunix_software); SAP device types (hp.com ows XP (SP2+), Windows Server 2003 (SP1+), Windows 10 perating system compatible hard win Lion; 1 GB available hard disk space; operating 2 10 internal scalable fonts in HP Postscript level 3 10 internal scalable fonts in HP Postscript level 3 10 internal scalable fonts in HP Postscript level 3 11 internal scalable fonts in HP Postscript level 3 12 internal scalable fonts in HP Postscript level 3 13 internal scalable fonts in HP Postscript level 3 14 internal scalable fonts in HP Postscript level 3 15 internal scalable fonts in HP Postscript level 3 16 internal scalable fonts in HP Postscript level 3 17 internal scalable fonts in HP Postscript level 3 18 internal scalable fonts in HP Postscript level 3 19 internal scalable fonts in HP Postscript level 3 10 internal scalable fonts in HP Postscript level 3 10 internal scalable fonts in HP Postscript level 3 11 internal scalable fonts in HP Postscript level 3 12 internal scalable fonts in HP Postscript level 3 13 internal scalable fonts in HP Postscript level 3 14 internal scalable fonts in HP Postscript level 3 15 internal scalable fonts in HP Postscript level 3 16 internal scalable fonts in HP Postscript level 3 17 internal scalable fonts in HP Postscript | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1 chase of a hardware accessory   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wireles  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)   |
| Standard connectivity  Network capabilities  Wireless capability Modem Memory Processor speed Duty cycle (monthly, A4) <sup>6</sup> Recom monthly page volume <sup>7</sup> Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box <sup>4</sup> Warranty features Compatible operating systems Winimum system requirements Fonts and Typefaces Control panel Software included   | Not Applicable  Paper (color, letterhed  Paper (color, letterhed  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; l  Windows 8, Windows 7, Windows Vista, Windows 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unkromdelscripts, hp.com/go/pl/  PC: Windows 8, Windows 7, Windows Vista, Windows Wista, Windows Vista, Windows Vi | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure  80i Up to 5000 Up to 5000 Up to 5000 Up to 5000 Tray 1: 3 × 5 to 12.3 × 18.5 in; Tray 2: 5.8 × 8.3 1 Standard 29.3 × 26.8 × 45.7 in (745 × 681 × 1160 mm); Max: 36.1 × 40.6 × 45.7 in (745 × 681 × 1160 mm); 192.3 lb (87.1 kg)  19 Black LaserJet Toner Cartridge (10,000 pages); CD-ROM; Power cord. M725f, M7252 & None-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows Space; operating system support see: Citrix and Windows Tetdirectunix_software); SAP device types (lp_comows XP (SP2+), Windows Server 2003 (SP1+), Windows Space; operating system compatible hardw in Lion; 1 68 available hard disk space; operating so 21 internal scalable forts in HP Postscript level 3 en onal font solutions on sailable via sthird-party flash on in; rotating (adjustable angle) display; illuminated Her, HP PCL 6 discrete driver, Mac SW Link to Web, [P   | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1-hase of a hardware accessory 33.6 kbps  GB 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 1,00 sheets 29.3 x 26.8 x Max; 36.1 x 40.6 206.3 lb (92: 35 kg) 1-dardware Installation Guide, Support flyer, W/1725z+: Same as above plus Telecom cable 1-site warranty Server 2008 (32 and 64-bit), Windows Server 2 1 companies of the support of t | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wirele  re, labels, transparency, veltum  x 17 in  46.9 in (745 x 681 x 1192 mm);  |
| Standard connectivity  Network capabilities  Wireless capability Modem Memory Processor speed Outy cycle (monthly, A4)* Network capability Modemory Processor speed Outy cycle (monthly, A4)* Network capability Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Neight What's in the box* Narranty features Compatible operating systems Minimum system equirements Control panel Control panel Coftware included Operating humidity ranges   | Not Applicable  Paper (color, letterhed  Paper (color, letterhed  24.2 × 25.6 × 24 in (614 × 649 × 609 mm)  Max: 34.1 × 38.9 × 24 in (865 × 989 × 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; I  Windows 8, Windows 7, Windows Vista, Window 10.6, OS X Lion, OS X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/li  PC: Windows 8, Windows 7, Windows Vista, Window 105 internal TrueType fonts scalable in HP PCL, 9  Vista 8 Fonts (Calibri, Cambria); additi 8.0-in (20.3 cm) color LCD with touchscree  Windows Install  | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure  800 Up to 200 Up to 5000 t  10  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1-hase of a hardware accessory 33.6 kbps  GB 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 1,00 sheets 29.3 x 26.8 x Max; 36.1 x 40.6 206.3 lb (92: 35 kg) 1-dardware Installation Guide, Support flyer, W/1725z+: Same as above plus Telecom cable 1-site warranty Server 2008 (32 and 64-bit), Windows Server 2 1 companies of the support of t | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wirele  se, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm); x 46.9 in (917 x 1032 x 1192 mm)  225.8 lb (102.42 kg)  arranty guide; Printer documentation and software on  2008 R2 (64-bit), Windows Server 2012 (64-bit); Mac OS X  vell.com/print); Linux (hplip.net); UNIX (hp.com/go/unib ePrint Mobile Driver (hp.com/go/eprintmobiledriver) Windows Server 2012 (64-bit); 200 MB available hard on  nents, CD-ROM/DVD-ROM or Internet, see apple.com icode Fonts (Andale Mono WorldType); 2 Internal Windo unulation available at hp.com/go/laserjetfonts enu); Easy Access USB; Hardware Integration Pocket i), Note: No Mac SW inbox  |
| Standard connectivity  Network capabilities  Wireless capability Modern Memory Processor speed Duty cycle (monthly, A4) <sup>5</sup> Recom monthly page volume <sup>7</sup> Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box <sup>6</sup> Warranty features Compatible operating systems Minimum system equirements Fonts and Typefaces Control panel Coftware included Invironmental ranges Operating humidity range: Non-operating humidity range: Non-operating humidity range:  | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhei  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; I  Windows 8, Windows 7, Windows Vista, Windov 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unkmodelscripts, hp.com/go/I  PC: Windows 8, Windows 7, Windows Vista, Windov  Mac: Mac 05 X 10.6, 05 X Lion, 05 X Mounta 105 internal TrueType fonts scalable in HP PCL, 9  Vista 8 Fonts (Calibri, Cambria); additi 8.0-in (20.3 cm) color LCD with touchscree  Windows Install  20 to 80% RH e: 10 to 90% RH   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networki Optional, enabled with pure  80 Up to 200 Up to 5000 Up to 5000 Up to 5000 Up to 5000 Tray 1: 3 × 5 to 12.3 × 18.5 in; Tray 2: 5.8 × 8.3 t Standard 29.3 × 26.8 × 45.7 in (745 × 681 × 1160 mm) Max: 36.1 × 40.6 × 45.7 in (917 × 1032 × 1160 mm) 192.3 lb (87.1 kg) 4P Black LaserJet Toner Cartridge (10,000 pages); (CD-ROM; Power cord, M725f, M7252 & N One-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows to operating system support see: Citrix and Windows T etdirectunix_software); SAP device types (hp.com ows XP (SP2+), Windows Server 2003 (SP1+), Windows Server 2003 (SP1+), Windows 10 (SP2+), Windows Server 2003 (SP1+), Windows 12 (Internal scalable fonts in HP Postscript level 3 en onal font solutions available with tird-party flash n n; rotating (adjustable angle) display; illuminated H er, HP PCL 6 discrete driver, Mac SW Link to Web, [P  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1 chase of a hardware accessory   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wirele  se, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)  |
| Standard connectivity  Network capabilities  Wireless capability Modem Memory Processor speed Duty cycle (monthly, A4) <sup>6</sup> Networm monthly page volume <sup>7</sup> Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box <sup>4</sup> Warranty features Compatible operating systems  Alinimum system equirements  Fonts and Typefaces Control panel Software included Invironmental ranges Operating humidity range: Non-operating humidity range.  | Not Applicable  Paper (color, letterhed  Paper (color, letterhed  Paper (color, letterhed  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; l  Windows 8, Windows 7, Windows Vista, Window 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/lp)  PC: Windows 8, Windows 7, Windows Vista, Window 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/lp)  PC: Windows 8, Windows 7, Windows Vista, Window 10.5 internal TrueType fonts scalable in HP PCL, 9  Vista 8 Fonts (Calibri, Cambria); additit 8.0-in (20.3 cm) color LCD with touchscree  Windows Install  20 to 80% RH  e: 10 to 90% RH  idity range: 30 to 70% RH  | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure  80 Up to 5000 Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 × 5 to 12.3 × 18.5 in; Tray 2: 5.8 × 8.3 t Standard 29.3 × 26.8 × 45.7 in (745 × 681 × 1160 mm); Max: 36.1 × 40.6 × 45.7 in (745 × 681 × 1160 mm); 19.3 lb (87.1 kg)  19 Black LaserJet Toner Cartridge (10,000 pages); CD-ROM; Power cord. M725f, M7252 & N One-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows to perating system support see: Citrix and Windows T etdirectuniz, software); SAP device types (lpb.com ows XP (SP2+), Windows Server 2003 (SP1+), Windows space; operating system compatible hardw in Lion; 1 GB available hard disk space; operating s 12 internal scalable fonts in HP Postscript level 3 en onal font solutions available via third-party flash in, rotating (adjustable angle) display; illuminated H er, HP PCL 6 discrete driver, Mac SW Link to Web, [P Acoustic press Acoustic press  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1-hase of a hardware accessory 33.6 kbps  GB 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 11,7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 1,00 sheets 29.3 x 26.8 x Max: 36.1 x 40.6 206.3 lb (92.35 kg) 1-dardware Installation Guide, Support flyer, W.1725z+' Same as above plus Telecom cable 1-site warranty Server 2008 (32 and 64-bit), Windows Server 2 1 company of the  | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wirele  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)  |
| Standard connectivity  Network capabilities  Wireless capability  Modern  Alemory  Processor speed  Media type  Media type  Media type  Media type  Media type  Media syes  ADF capacity  Processor speed  Process   | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhei  24.2 × 25.6 × 24 in (614 × 649 × 609 mm)  Max: 34.1 × 38.9 × 24 in (865 × 389 × 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; I  Windows 8, Windows 7, Windows Vista, Window 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unkmodelscripts, hp.com/go/i  PC: Windows 8, Windows 7, Windows Vista, Window  Mac: Mac OS X 10.6, 05 X Lion, 05 X Mountain 105 internal TrueType fonts scalable in HP PCL, 9  Vista 8 Fonts (Calibri, Cambria); additi 8.0-in (20.3 cm) color LCD with touchscree  Windows Install  20 to 80% RH e: 10 to 90% RH e: 10 to 90% RH e: 50 to 91° F (10 to 32.5° C)  | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networki Optional, enabled with pure  80 Up to 200 Up to 5000 Up to 5000 Up to 5000 Up to 5000 Tray 1: 3 × 5 to 12.3 × 18.5 in; Tray 2: 5.8 × 8.3 t Standard 29.3 × 26.8 × 45.7 in (745 × 681 × 1160 mm) Max: 36.1 × 40.6 × 45.7 in (917 × 1032 × 1160 mm) 192.3 lb (87.1 kg) 4P Black LaserJet Toner Cartridge (10,000 pages); (CD-ROM; Power cord, M725f, M7252 & N One-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows to operating system support see: Citrix and Windows T etdirectunix_software); SAP device types (hp.com ows XP (SP2+), Windows Server 2003 (SP1+), Windows Server 2003 (SP1+), Windows 10 (SP2+), Windows Server 2003 (SP1+), Windows 12 (Internal scalable fonts in HP Postscript level 3 en onal font solutions available with tird-party flash n n; rotating (adjustable angle) display; illuminated H er, HP PCL 6 discrete driver, Mac SW Link to Web, [P  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1 chase of a hardware accessory   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wirele  le, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)  |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Ilemory  rocessor speed  uty cycle (monthly, A4) <sup>5</sup> lecom monthly page volume <sup>7</sup> Paper handing  Media type  Media weight  Custom media sizes  ADF capacity  Dimensions (W x D x H)  Weight  What's in the box <sup>6</sup> Warranty features  compatible operating ystems  Ilinimum system equirements  onts and Typefaces  ontrol panel  oftware included  vironmental ranges  Operating humidity rang  Recommended operating hun  Operating temperature range  Recommended operating tem  | Not Applicable  Paper (color, letterher  Paper (color, letterher  Paper (color, letterher  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 889 x 609 mm)  119.3 ib (54.11 kg)  M725dn: HP LaserJet Enterprise MFP M725; I  Windows 8, Windows 7, Windows Vista, Window 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/uhxmodelscripts, hp.com/go/pl  PC: Windows 8, Windows 7, Windows Vista, Wind | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure  80 Up to 5000 Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 × 5 to 12.3 × 18.5 in; Tray 2: 5.8 × 8.3 t Standard 29.3 × 26.8 × 45.7 in (745 × 681 × 1160 mm); Max: 36.1 × 40.6 × 45.7 in (745 × 681 × 1160 mm); 19.3 lb (87.1 kg)  19 Black LaserJet Toner Cartridge (10,000 pages); CD-ROM; Power cord. M725f, M7252 & N One-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows to perating system support see: Citrix and Windows T etdirectuniz, software); SAP device types (lpb.com ows XP (SP2+), Windows Server 2003 (SP1+), Windows space; operating system compatible hardw in Lion; 1 GB available hard disk space; operating s 12 internal scalable fonts in HP Postscript level 3 en onal font solutions available via third-party flash in, rotating (adjustable angle) display; illuminated H er, HP PCL 6 discrete driver, Mac SW Link to Web, [P Acoustic press Acoustic press  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) hase of a hardware accessory 33.6 kbps  GB 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 100 sheets 29.3 x 26.8 x Max: 36.1 x 40.6 206.3 lb (92.35 kg) 14ardware Installation Guide, Support flyer, Width 192.5 sheets 29.5 x 26.8 x Max: 36.1 x 40.6 206.3 lb (92.35 kg) 14ardware Installation Guide, Support flyer, Width 192.5 sheets 29.5 x 26.8 x Max: 36.1 x 40.6 206.3 lb (92.35 kg) 14ardware Installation Guide, Support flyer, Width 192.5 sheets 29.5 x 26.8 x Max: 36.1 x 40.6 206.3 lb (92.35 kg) 15.5 the variantly Server 2008 (32 and 64-bit), Windows Server 2 erminal Services (1p. com/go/upal); Novell (nover) 19.0 stem compatible hardware system requirem nulation (Euro symbol built-in); 1 internal University or 19.5 the system requirem of the thome mostscript emulation driver & Installer on Webure emissions by stander (active, printing): ure emissions by stander (active, printing): ure emissions by stander (active, printing): ure emissions by stander (ready):   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host net and Gig Links; IPsec (standard); 802.11b/g/n wirele  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm); x 46.9 in (917 x 1032 x 1192 mm)  225.8 lb (102.42 kg) arranty guide; Printer documentation and software on  2008 R2 (64-bit), Windows Server 2012 (64-bit); Mac OS X vell.com/iprint); Linux (hplip.net); UNIX (inp.com/go/unib ePrint Mobile Driver (inp.com/go/eprintobiledriver) Windows Server 2012 (64-bit); 200 MB available hard on  ments, CD-ROM/DVD-ROM or Internet, see apple.com icode Fonts (Andale Mono WorldType); 2 Internal Windom ulation available at hp.com/go/laserjetfonts enu); Easy Access USB; Hardware Integration Pocket ol), Note: No Mac SW inbox  54 dB(A) 36 dB(A)  Built-in power supply 110-volt input voltage: (Option #BGJ, #201) 110 to 12: VAC (+/- 10%), So/60 Hz (+/- 2 Hz); 220-volt input volt   |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Iemory  Trocessor speed  uty cycle (monthly, A4) <sup>6</sup> ecom monthly page volume?  Pager handing  Media type  Media weight  Custom media sizes  ADF capacity  Immensions (W x D x H)  Jeight  Jhat's in the box <sup>6</sup> Jarranty features  compatible operating  systems  Inimum system  equirements  onts and Typefaces  ontrol panel  oftware included  vironmental ranges  Operating humidity range:  Non-operating humidity range  Recommended operating tum  Operating temperature range  Recommended operating tum  Operating temperature range  Recommended operating tum  Operating temperature range  Recommended operating tum   | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhei  24.2 × 25.6 × 24 in (614 × 649 × 609 mm)  Max: 34.1 × 38.9 × 24 in (865 × 389 × 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; I  Windows 8, Windows 7, Windows Vista, Window 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unkmodelscripts, hp.com/go/i  PC: Windows 8, Windows 7, Windows Vista, Window  Mac: Mac OS X 10.6, 05 X Lion, 05 X Mountain 105 internal TrueType fonts scalable in HP PCL, 9  Vista 8 Fonts (Calibri, Cambria); additi 8.0-in (20.3 cm) color LCD with touchscree  Windows Install  20 to 80% RH e: 10 to 90% RH e: 10 to 90% RH e: 50 to 91° F (10 to 32.5° C)  | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure  80 Up to 5000 Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 × 5 to 12.3 × 18.5 in; Tray 2: 5.8 × 8.3 t Standard 29.3 × 26.8 × 45.7 in (745 × 681 × 1160 mm); Max: 36.1 × 40.6 × 45.7 in (745 × 681 × 1160 mm); 19.3 lb (87.1 kg)  19 Black LaserJet Toner Cartridge (10,000 pages); CD-ROM; Power cord. M725f, M7252 & N One-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows to perating system support see: Citrix and Windows T etdirectuniz, software); SAP device types (lpb.com ows XP (SP2+), Windows Server 2003 (SP1+), Windows space; operating system compatible hardw in Lion; 1 GB available hard disk space; operating s 12 internal scalable fonts in HP Postscript level 3 en onal font solutions available via third-party flash in, rotating (adjustable angle) display; illuminated H er, HP PCL 6 discrete driver, Mac SW Link to Web, [P Acoustic press Acoustic press  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1 chase of a hardware accessory   | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host net and Gig Links; IPsec (standard); 802.11b/g/n wirele  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm); x 46.9 in (917 x 1032 x 1192 mm) 225.8 lb (102.42 kg) arranty guide; Printer documentation and software on  2008 R2 (64-bit), Windows Server 2012 (64-bit); Mac OS X vell.com/iprint); Linux (hplip.net); UNIX (hp.com/go/unbe ePrint Mobile Driver (hp.com/go/eprintmobiledriver) Windows Server 2012 (64-bit); 200 MB available hard on: nents, CD-ROM/DVD-ROM or Internet, see apple.com icode Fonts (Andale Mono WorldType); 2 Internal Window icode Fonts (Andale Mono WorldType); 2 Internal Window ulation available at hp.com/go/laserjetfonts enu); Easy Access USB; Hardware Integration Pocket i), Note: No Mac SW inbox  54 dB(A)  Built-in power supply 110-volt input voltage; (Option #BGJ, #201) 110 to 12; VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input volt (Option #AAZ) 220 to 240 VAC (+/- 10%), 50/60 Hz (+/-)   |
| Standard connectivity  Network capabilities  Wireless capability  Modem  Memory  Processor speed Duty cycle (monthly, A4) <sup>6</sup> Recommently page volume?  Paper handing  Media type  Media weight  Custom media sizes  ADF capacity  Dimensions (W x D x H)  Weight  What's in the box <sup>a</sup> Warranty features  Compatible operating  yestems  Winimum system  equirements  Control panel  Fortware included  Invironmental ranges  Operating humidity range:  Non-operating humidity range  Recommended operating tun  Operating temperature range  Recommended operating hum  Operating temperature range  Recommended operating tem  Storage temperature range  Recommended operating tem  Storage temperature range  Recommended operating tem  Storage temperature range  | Not Applicable  Paper (color, letterher  Paper (color, letterher  Paper (color, letterher  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 889 x 609 mm)  119.3 ib (54.11 kg)  M725dn: HP LaserJet Enterprise MFP M725; I  Windows 8, Windows 7, Windows Vista, Window 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/uhxmodelscripts, hp.com/go/pl  PC: Windows 8, Windows 7, Windows Vista, Wind | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure  80 Up to 5000 Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 × 5 to 12.3 × 18.5 in; Tray 2: 5.8 × 8.3 t Standard 29.3 × 26.8 × 45.7 in (745 × 681 × 1160 mm); Max: 36.1 × 40.6 × 45.7 in (745 × 681 × 1160 mm); 19.3 lb (87.1 kg)  19 Black LaserJet Toner Cartridge (10,000 pages); CD-ROM; Power cord. M725f, M7252 & N One-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows to perating system support see: Citrix and Windows T etdirectuniz, software); SAP device types (lpb.com ows XP (SP2+), Windows Server 2003 (SP1+), Windows space; operating system compatible hardw in Lion; 1 GB available hard disk space; operating s 12 internal scalable fonts in HP Postscript level 3 en onal font solutions available via third-party flash in, rotating (adjustable angle) display; illuminated H er, HP PCL 6 discrete driver, Mac SW Link to Web, [P Acoustic press Acoustic press  | elephone Handset Supported: No; Fax Telej  00T network; 1 Foreign Interface; 1 Hardwar  Base-T; 802.3az (EEE) support on Fast Ether  19 (optional)  chase of a hardware accessory  33.6 kbps  68  0 MHz  0,000 pages  0 20,000 pages  0 20,000 pages  0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7  100 sheets  29.3 x 26.8 x  Max: 36.1 x 40.6  206.3 lb (92.35 kg)  lardware Installation Guide, Support flyer, W  1725z+: Same as above plus Telecom cable  -site warranty  server 2008 (32 and 64-bit), Windows Server 2  erminal Services (thp.com/go/sap/print). HP  ows Server 2008, Windows Server 2008 (2)  are system requirements, see microsoft.com  system requirements, see microsoft.com  sultation (Euro synthem system requirements). The requirements of the system requirements of the Home mostscript emulation driver & Installer on Web  sure emissions bystander (active, printing): ure emissions bystander (ready):  ype:  equired:  | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host net and Gig Links; IPsec (standard); 802.11b/g/n wirele  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)  |
| Standard connectivity  Network capabilities  Wireless capability Modern Memory Processor speed Duty cycle (monthly, A4) <sup>4</sup> Recom monthly page volume <sup>7</sup> Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box <sup>4</sup> Warranty features Compatible operating systems Minimum system equirements Fonts and Typefaces Control panel Software included Nor-operating humidity range: Non-operating humidity rang Recommended operating tem Storage temperature range: Recommended operating tem Storage temperature range: Coustic <sup>10</sup> Storage temperature range: Coustic <sup>10</sup> Cous | Not Applicable  Paper (color, letterhed)  Paper (color, letterhed)  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; l  Windows 8, Windows 7, Windows Vista, Windows 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unkmodelscripts, hp.com/go/pl/  PC: Windows 8, Windows 7, Windows Vista, Windows 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unkmodelscripts, hp.com/go/pl/  PC: Windows 8, Windows 7, Windows Vista, Windows 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unkmodelscripts, hp.com/go/pl/  PC: Windows 8, Windows 7, Windows Vista, Windows Vista, Windows Vista, Windows Install 105 internal TrueType fonts scalable in HP PCL, 9  Vista 8 Fonts (Calibri, Cambria); additional 105 internal TrueType fonts scalable in HP PCL, 9  Vista 8 Fonts (Calibri, Cambria); additional 105 internal TrueType fonts scalable in HP PCL, 9  Vista 8 Fonts (Calibri, Cambria); additional 105 internal TrueType fonts scalable in HP PCL, 9  Vista 8 Fonts (Calibri, Cambria); additional 105 internal TrueType fonts scalable in HP PCL, 9  Vista 8 Fonts (Calibri, Cambria); additional 105 internal TrueType fonts scalable in HP PCL, 9  Vista 8 Fonts (Calibri, Cambria); additional 105 internal TrueType fonts scalable in HP PCL, 9  Vista 8 Fonts (Calibri, Cambria); additional 105 internal TrueType fonts scalable in HP PCL, 9  Vista 9 FOT ROW   | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networkin Optional, enabled with pure  80 Up to 5000 Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 × 5 to 12.3 × 18.5 in; Tray 2: 5.8 × 8.3 t Standard 29.3 × 26.8 × 45.7 in (745 × 681 × 1160 mm); Max: 36.1 × 40.6 × 45.7 in (745 × 681 × 1160 mm); 19.3 lb (87.1 kg)  19 Black LaserJet Toner Cartridge (10,000 pages); CD-ROM; Power cord. M725f, M7252 & N One-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows to perating system support see: Citrix and Windows T etdirectuniz, software); SAP device types (lpb.com ows XP (SP2+), Windows Server 2003 (SP1+), Windows space; operating system compatible hardw in Lion; 1 GB available hard disk space; operating s 12 internal scalable fonts in HP Postscript level 3 en onal font solutions available via third-party flash in, rotating (adjustable angle) display; illuminated H er, HP PCL 6 discrete driver, Mac SW Link to Web, [P Acoustic press Acoustic press  | elephone Handset Supported: No; Fax Telej 00T network; 1 Foreign Interface; 1 Hardwar 18ase-T; 802.3az (EEE) support on Fast Ether 19 (optional) 1-hase of a hardware accessory 33.6 kbps 68 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 1,100 sheets 29.3 x 26.8 x Max: 36.1 x 40.6 206.3 lb (92.35 kg) 1-ardware Installation Guide, Support flyer, W/1725z+: Same as above plus Telecom cablesite warranty Server 2008 (32 and 64-bit), Windows Server 2 emgins Services (1p. com/go/upd); Novell (nover) 10 yestem completes, hp. com/go/upd); Novell (nover) 10 yestem requirements, see microsoft.com 10 yestem compatible hardware system requirential thin emory cards; HP Laser Jet Fonts and IPDS En ome button (for quick return to the Home mostscript emulation driver & Installer on Web 11 yere emissions bystander (active, printing): 12 yee: 13 equired:  | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host met and Gig Links; IPsec (standard); 802.11b/g/n wireles  re, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm);  x 46.9 in (917 x 1032 x 1192 mm)   |
| Network capabilities Wireless capability Modem Memory Processor speed Duty cycle (monthly, A4)s Recom monthly page volume? Paper handing Media type Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the boxs Warranty features Compatible operating systems Minimum system requirements Fonts and Typefaces Control panel Software included nvironmental ranges Operating humidity range: Non-operating humidity range: Non-operating humidity range: Recommended operating hum Operating temperature range Recommended operating tem Storage temperature range: coustic 19 Acoustic power emissions:  | Via HP Jetdirect Ethernet embedded print serve  Not Applicable  Paper (color, letterhes)  24.2 x 25.6 x 24 in (614 x 649 x 609 mm)  Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm)  119.3 lb (54.11 kg)  M725dn: HP Laser Jet Enterprise MFP M725; I  Windows 8, Windows 7, Windows Vista, Window 10.6, OS X Lion, OS X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/Ji  PC: Windows 8, Windows 7, Windows Vista, Window 10.6, OS X Lion, OS X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/Ji  PC: Windows 8, Windows 7, Windows Vista, Windows 10.6, OS X Lion, OS X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/Ji  Windows 8, Windows 7, Windows Vista, Windows 10.6, OS X Lion, OS X Mountain 105 internal TrueType fonts scalable in HP PCL, government of the lates hp.com/go/Windows Install  Wista 8 Fonts (Calibri, Cambria); addition and the lates hp.com/go/Windows Install  20 to 80% RH e: 10 to 90% RH indity range: 30 to 70% RH indity range: 30 to 70% RH indity range: 30 to 70% RH indity range: 50 to 91° F (10 to 32.5° C) 32 to 140° F (0 to 60° C)  46.8 B(A) 7.1 B(A)  | peed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 r (standard) supports: 10Base-T, 100Base-Tx, 100C networki Optional, enabled with pure  80i Up to 200 Up to 5000 Up to 5000 Up to 5000 Up to 5000 Tray 1: 3 × 5 to 12.3 × 18.5 in; Tray 2: 5.8 × 8.3 t Standard 29.3 × 26.8 × 45.7 in (745 × 681 × 1160 mm) 192.3 lb (87.1 kg) 4P Black LaserJet Toner Cartridge (10,000 pages); CD-ROM; Power cord. M725f, M7252 & N 0ne-year or vs XP (SP2+), Windows Server 2003 (SP1+), Windows to perating system support see: Citrix and Windows Tetdirectunix_software); SAP device types (lp_coms ows XP (SP2+), Windows Server 2003 (SP1+), Win | elephone Handset Supported: No; Fax Telej  00T network; 1 Foreign Interface; 1 Hardwar  Base-T; 802.3az (EEE) support on Fast Ether  19 (optional)  chase of a hardware accessory  33.6 kbps  GB  0 MHz  0,000 pages  0 20,000 pages  0 20,000 pages  0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7  1,100 sheets  29.3 x 26.8 x  Max: 36.1 x 40.6  206.3 lb (92.35 kg)  dardware Installation Guide, Support flyer, W1725z+2 Same as above plus Telecom cable  1-site warranty  Server 2008 (32 and 64-bit), Windows Server 2  Ferminal Services (hp.com/go/upd); Novell (nov 190/sap/drivers, hp.com/go/sap/print); HP  200 Server 2008, Windows Server 2008 R2, are system requirem unulation (Euro symbol built-in); 1 internal Unitemory cards; HP Laser Jet Fonts and IPDS Enome button (for quick return to the Home mostscript emulation driver & Installer on Web  ure emissions bystander (active, printing):  uppe:  equired:  | phone Mode Supported: No  re Integration Pocket; 2 Internal USB Host net and Gig Links; IPsec (standard); 802.11b/g/n wireles net and Gig Links; IPsec (standard); 802.11b/g/n wireles net and Gig Links; IPsec (standard); 802.11b/g/n wireles net, labels, transparency, vellum  x 17 in  46.9 in (745 x 681 x 1192 mm); x 46.9 in (745 x 681 x 1192 mm); y 25.8 ib (102.42 kg) arranty guide; Printer documentation and software on  2008 R2 (64-bit), Windows Server 2012 (64-bit); Mac OS X vell.com/Iprint); Linux (hplip.net); UNIX (hp.com/go/unix ePrint Mobile Driver (hp.com/go/eprintmobiledriver) Windows Server 2012 (64-bit); 200 MB available hard d net. nets, CD-ROM/DVD-ROM or Internet, see apple.com icode Fonts (Andale Mono WorldType); 2 Internal Windo nulation available at hp.com/go/laserjetfonts nul.; Easy Access USB; Hardware Integration Pocket nul, Rasy Access USB; Hardware Integration Pocket nul, Rote: No Mac SW inbox  54 dB(A) 36 dB(A)  Built-in power supply 110-volt input voltage: (Option #BGJ, #201) 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage) (Not dual voltage, power supply varies by part number # Option code identifier)   |

Measured using ISO/IEC 24734, excludes first set of test documents. For more information see <a href="https://documents.peed-universal-u















